EV9619-01 OW200L Filter Cartridge		
	OW200L Replacement Cartridge: EV9619-01	BENEFITS Provides sparkling, fresh, premium quality drinking water. Ideal for bottleless water coolers and drinking fountains Everpure's unique filter blend using activated carbon reduces chlorine taste and odor and other offensive contaminants Reduces lead to below the Federal Action Level of 15 ppb Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size Reduces health contaminants such as Cryptosporidium and Giardia cysts and effectively reduces Trihalomethanes (THMs) Does not remove fluoride from the water Inhibits scale build-up in water using appliances (as tested by Everpure) Sanitary cartridge replacement is simple, quick and clean NSF Certified under NSF/ANSI Standards 42 and 53
INSTALLATION TIPS Never use saddle valve for connection Use 3/8" water line Install vertically with cartridge hanging down Allow 2-1/2" clearance below the cartridge for easy cartridge replacement Flush OW200L cartridge by running water through filter for three minutes at full flow	OPERATION TIPS Change cartridges on a regular 6 month preventative maintenance program Change cartridges when capacity is reached or when pressure falls below to psi Service flow rate must not exceed 0.5 gpm Always flush the filter cartridge at time of installation and cartridge change	APPLICATION/SIZING For office water applications Bottleless water coolers and drinking fountains Rated Capacity: 480 gallons (1,816 L)

OW200L Filter Cartridge

S P E C I F I C A T I O N S

Overall Dimensions: 17"H x 3.25"Diameter

Service Flow Rate: Maximum 0.5 gpm (1.9 Lpm)

Rated Capacity: 480 gallons

Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock

Maximum Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction Mechanical Filtration Unit

Nominal Particulate Reduction, Class I: 97.9% reduction of particles one-half micron and larger in size

Standard No. 53: Health Effects Chemical Reduction Unit Lead Reduction TTHM Reduction Mechanical Filtration Unit Cyst Reduction



Worldwide Headquarter : EVERPURE, LLC t040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323 - 7873 Tel (630) 307 - 3030 Fax (630) 307 - 3030 http://www.everpure.com In Europe: Everpure Europe bvba Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283.500 FAX: +32.(0).14.283.505 In Japan: Everpure Japan Inc. Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1-1103 JAPAN TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015